



**COLLECTION | HERRINGBONE  
COLOR | PASTEL**

Wood species | Oak  
Grade | Select & Better  
Constructions | Solid Hardwood Flooring  
Size | 19,05 x 82,55 x 412,75mm (¾" x 3 ¼" x 16 ¼")  
Finish | Silk Oil

**CONSTRUCTION : SOLID HARDWOOD FLOORING**

DIMENSIONS :			PACKAGING :	
			BOX	PALLET
Thickness	19,05 mm (¾")	Content:	1,5 m <sup>2</sup>	36 (54 m <sup>2</sup> )
Width	82,55 mm (3 ¼")	Weight	20 kg	746 kg
Length	412,75 mm (16 ¼")	H x W x L	213 x 344 x 434 mm	975 x 800 x 1750 mm
Cut angle	90°	Content:	16,14 sq.ft.	581,04 sq.ft.
Microbevel	0,5 mm	Weight	45 lb	1650 lb
Joint type	tongue and groove (T&G)	H x W x L	9" x 14" x 18"	39" x 32" x 69"

**DEVIATIONS :**

Deviation on Thickness	± 0,2 mm	EN 13226
Deviation on Width	± 0,2 mm	
Height Difference	≤ 0,2 % of width	ГОСТ 862.1
Cup	≤ 0,2 % of plank width	СТБ 1454
Bow	≤ 0,5 % of length	EN 13226
Spring	≤ 0,5 ‰ of length	

**CHARACTERISTICS :**

Fire resistance	Dfl-s1	EN 14342
Formaldehyde emission class	E1	
Pentachlorophenol content	None	
Thermal resistance	0,112 m <sup>2</sup> ·K/W	
Thermal conductivity	0,170 W/(m·K)	
Structural warranty	Lifetime	

**INSTALLATION :**



Glue down over concrete, plywood or wooden subfloor or nail down over wooden subfloor.  
Applicable above and on ground level.

**STORAGE AND USAGE :**



— Air humidity 45% – 55%  
— Temperature +18 °C – +22 °C

**FINISH : SILK OIL**

DESCRIPTION :	
Type of coating	UV-cured modified polyurethane-acrylate
Surface (finish) type	Semi-closed pores, wire brushed
Sheen	Silk matte 9-18 GU/85°
Finish warranty	-

**CLASSIFICATION SURFACE CHARACTERISTICS :**

Wear resistance	Not rated	EN 438-2
Scratch resistance	Not rated	EN 438
Slip resistance	50 (SRV dry)	EN 15676
Resistance to chemical agents	Class 5 (Except blue ink)	EN 13442
Repairability	Medium	

**MAINTENANCE AND CARE CONDITIONS :**

Maintenance of hardwood floors with Silk Oil finish assumes regular (daily if necessary) cleaning from dust and grit using a vacuum, followed by a thorough cleaning with Coswick Hardwood Floor Cleaner or other similar product. Floor surface areas that receive the most traffic and get worn down quicker, such as areas by the front door, hallways, kitchens etc., should be periodically renewed with special Coswick Restorative Oil. This product restores the protective surface film. Frequency of use depends on type of interior and intensity of foot traffic. For residential interiors, restorative cleaning should be done once in 3-5 years; for public and commercial interiors with intense foot traffic, it is recommended to use the product 2-4 times a year.

**GRADE : SELECT & BETTER**

DESCRIPTION :		DESCRIPTION :	
Sound sapwood	Permitted non-contrasting up to 25% of the plank area	Bark pocket	Permitted up to 10 mm in length, up to 3 mm in width, filled
Colour variation	Permitted slight colour variation	Pith	Permitted healthy heart
Knot	Permitted up to 10 mm, filled	Slope of grain	Permitted
Checks	Not permitted	Medullary ray	Permitted